

Annotation Processing: um dos segredos dos projetos Java Open Source

Eder Ignatowicz
Senior Software Engineer Red Hat

```
@Entity
@Table(name = "stock_daily_record", catalog = "edesign",
uniqueConstraints = @UniqueConstraint(columnNames = "DATE"))
public class StockDailyRecord implements java.io.Serializable {

    @Id
    @GeneratedValue(strategy = IDENTITY)
    @Column(name = "RECORD_ID", unique = true, nullable = false)
    public Integer getRecordId() {
        return this.recordId;
    }

    @ManyToOne(fetch = FetchType.LAZY)
    @JoinColumn(name = "STOCK_ID", nullable = false)
    public Stock getStock() {
        return this.stock;
    }

    @Column(name = "PRICE_CHANGE", precision = 6)
    public Float getPriceChange() {
        return this.priceChange;
    }

}
```

```
@Target({ElementType.TYPE})
@Retention(RetentionPolicy.RUNTIME)
public @interface Entity {
    String name() default "";
}
```

Annotations

Metadados

Tooling

Geração de Código

Eliminar Boilerplate

Annotations

Runtime
Compile time



```
@Target({ElementType.TYPE})
@Retention(RetentionPolicy.RUNTIME)
public @interface Entity {
    String name() default "";
}
```



JDora UnitTest Framework



DEMO GODS



**PLEASE LET THESE
DEMOS WORK**

Annotations

Runtime



Annotations

Compile Time

Annotation Processing

Annotation Processing

Parte da compilação

Escaneia os fontes por anotações


Criar novos arquivos



Capturar erros em compilação

Eliminar boilerplate <3

Annotatiion Processing

Não faz:
Injetar código
Modificar os fontes





```
package com.example;           // PackageElement

public class Foo {            // TypeElement

    private int a;             // VariableElement
    private Foo other;         // VariableElement

    public Foo () {}          // ExecutableElement

    public void setA ()        // ExecutableElement

}
```

```
//@SupportedAnnotationTypes(
    {"javax.persistence.Entity", "javax.persistence.OneToMany"})
@SupportedSourceVersion(SourceVersion.RELEASE_7)
public class JpaProcessor extends AbstractProcessor {

    @Override
    public void init(ProcessingEnvironment env) {
        super.init(env);
    }

    @Override
    public Set<String> getSupportedAnnotationTypes() {
        return new HashSet<String>() {{
            add(PrintMe.class.getCanonicalName());
        }};
    }

    @Override
    public boolean process(
        Set<? extends TypeElement> annotations,
        RoundEnvironment roundEnv) {
        //seu processamento
        return false; // continua processando?
    }
}
```

Annotations

Compile Time



E na prática?

KIE Group

Open source projects for business systems automation and management.



Drools 5 introduces the **Business Logic integration Platform** which provides a unified and integrated platform for **Rules, Workflow and Event Processing**. It's been designed from the ground up so that each aspect is a first class citizen, with no compromises.

[Drools team](#)



jBPM is a flexible Business Process Management (BPM) Suite. A business process allows you to model your business goals by describing the steps that need to be executed to achieve those goals, and the order of those goals are depicted using a flow chart...

[jBPM team](#)




OptaPlanner optimizes business resource usage. Every organization faces planning problems: provide products or services with a limited set of constrained resources. OptaPlanner optimizes such planning to do more business with less resources...

[Optaplanner team](#)



UberFire is a web based workbench framework inspired by Eclipse Rich Client Platform. This is a very strategic project for Drools & jBPM team, once this is the base technology for our next generation of web tooling.



Dashbuilder is a full featured web application for the visual composition of custom business dashboards. Data comes from heterogeneous sources of information such as JDBC databases or regular text files and can be displayed using different charting libraries.



uberfire

Preferences Framework

Preferences

Build, Execution, Deployment > Compiler

Resource patterns: `!?*.java;!?*.form;!?*.class;!?*.groovy;!?*.scala;!?*.flex;!?*.kt;!?*.clj;!?*.aj` 

Use ; to separate patterns and ! to negate a pattern. Accepted wildcards: ? — exactly one symbol; * — zero or more symbols; / — path separator; /**/ — any number of directories; <dir_name>:<pattern> — restrict to source roots with the specified name

Clear output directory on rebuild

Add @NotNull assertions

Automatically show first error in editor

Display notification on build completion

Make project automatically

(only works while not running / debugging)

Compile independent modules in parallel

(may require larger heap size)

Rebuild module on dependency change

Build process heap size (Mbytes):

700

Shared build process VM options:

User-local build process VM options (overrides Shared options):

Appearance & Behavior

Keymap

Editor

Plugins

Version Control

Build, Execution, Deployment

Build Tools

Cloud Test Lab

Compiler

Application Servers

Deployment

Arquillian Containers

Clouds

Coverage

Debugger

Required Plugins

Languages & Frameworks

Tools



Cancel

Apply

OK

Wires Admin Tools



Users



Permissions

1



Application Map



System



My Preferences



Shared Preferences

```
@WorkbenchPreference(identifier = "MyPreference",
                      bundleKey = "MyPreference.Label")
public class MyPreference implements BasePreference<MyPreference> {

    @Property(bundleKey = "MyPreference.Text",
              helpBundleKey = "MyPreference.Text.Help",
              validators = NotEmptyValidator.class,
              formOptions = PropertyFormOptions.DISABLED)
    String text;

    @Property(formType = PropertyFormType.BOOLEAN, bundleKey = "MyPreference.SendReports")
    boolean sendReports;

    @Property(formType = PropertyFormType.COLOR, bundleKey = "MyPreference.BackgroundColor")
    String backgroundColor;

    @Property(formType = PropertyFormType.NATURAL_NUMBER, bundleKey = "MyPreference.Age")
    int age;

    @Property(formType = PropertyFormType.SECRET_TEXT, bundleKey = "MyPreference.Password")
    String password;

    @Property(bundleKey = "MyPreference.MyInnerPreference")
    MyInnerPreference myInnerPreference;

    @Property(shared = true, bundleKey = "MyPreference.MySharedPreference")
    MySharedPreference mySharedPreference;

    @Override
    public MyPreference defaultValue(final MyPreference defaultValue) {
        defaultValue.text = "text";
        defaultValue.sendReports = true;
        defaultValue.backgroundColor = "ABCDEF";
        defaultValue.age = 27;
        defaultValue.password = "password";
        defaultValue.myInnerPreference.text = "text";

        return defaultValue;
    }
}
```

```
public class MyServerBean {  
  
    @Inject  
    private MyPreference myPreference;  
  
    public void load() {  
        // Loads the preference content from the file system  
        myPreference.load();  
  
        myPreference.text = "text";  
        myPreference.sendReports = true;  
        myPreference.backgroundColor = "ABCDEF";  
        myPreference.age = 27;  
        myPreference.password = "password";  
        myPreference.myInnerPreference.text = "text";  
        myPreference.myInheritedPreference.text = "text";  
        myPreference.myInheritedPreference.myInnerPreference2.text = "text";  
        myPreference.myInheritedPreference.myInnerPreference2.myInheritedPreference2.text =  
        "text";  
  
        // Saves the modified preference content.  
        myPreference.save();  
    }  
}
```

Wires Admin Tools



Users



Permissions

1



Application Map



System



My Preferences



Shared Preferences

My Preference

- My Preference
 - My Inner Preference inside My Preference
 - My Shared Preference inside My Preference
 - My Inner Preference 2 inside My Shared Preference
 - My Shared Preference 2

My Preference

filter properties...

> Properties

Text	<input type="text" value="text"/>
Send reports?	<input checked="" type="checkbox"/>
Background color	<input type="color" value="ABCDEF"/> ABCDEF
Age	<input type="text" value="27"/>
Password	<input type="password" value="....."/>

Save **Cancel**

Überfire UI Components

Perspective

The Drools Workbench interface is divided into three main sections:

- Screen (Left):** Contains the Project Explorer, which lists various project components like DRL, Data Objects, and Guided Decision Tables.
- Editor (Center):** Displays the "Pricing loans.gdst - Guided Decision Tables" editor. It shows a "Decision table" named "Pricing loans" with columns: #, Description, application : LoanApplication, income : IncomeSource, Loan approved, LMI, and rate. There are four rows of data:

#	Description	application : LoanApplication	income : IncomeSource	Loan approved	LMI	rate			
amount min	amount max	period	deposit max	income					
1		131000	200000	30	20000	Asset	true	0	2
2		10000	100000	20	2000	Job	true	0	4
3		100001	130000	20	3000	Job	false	10	6
4		100001	130000	20	3000	Job	false	10	6
- Screen (Right):** Shows the "Analysis" results, indicating that rows 3 and 4 are subsumptant. It also lists missing range errors for rows 1, 2, 3, and 4.

Messages: A section at the bottom left of the central editor area displays the message "Affected rows:3, 4".

Editor Labels: The central editor area is labeled "Editor" and has a yellow background.

Screen Labels: The left and right side panels are labeled "Screen" and have red backgrounds.


Baseado em Contratos

Screen -> Interface WorkbenchScreenActivity

Editor -> Interface WorkbenchEditorActivity

Perspective -> Interface PerspectiveActivity

```
@WorkbenchPerspective(identifier = "HomePerspective", isDefault  
= true)  
@Templated  
public class HomePerspective implements IsElement {  
  
    @Inject  
    @DataField  
    @WorkbenchPanel(parts = "MoodScreen?uber=fire&uber1=fire1")  
    Div moodScreen;  
  
    @Inject  
    @DataField  
    @WorkbenchPanel(parts = "HomeScreen?uber=fire")  
    Div homeScreen;  
  
    @Inject  
    @DataField  
    @WorkbenchPanel(parts = "AnotherScreen")  
    Div anotherScreen;  
}
```



```
@JsType  
public interface PerspectiveActivity{  
  
    PerspectiveDefinition  
    getDefaultPerspectiveLayout();  
  
    @Override  
    default String getName() {  
        return  
    getDefaultPerspectiveLayout().getName();  
    }  
  
    boolean isDefault();  
  
    Menus getMenus();  
  
    ToolBar getToolBar();  
}
```



Annotations



Reflection



Annotation Processors



Open Source



Obrigado! <3

Eder Ignatowicz
@ederign



redhat.[®]